

SyncServer Model Comparison

Features		S80	S600	S650*
Time protocols	NTP server	■	■	■
	NTP peering/client		■	■
	NTP requests/second capacity with hardware time stamping	500	10,000	10,000
	Optional NTP requests/second capacity (NTP Reflector)**	1,000	360,000	360,000
	PTP output or input (software licenses)		○	○
Time references (inputs)	GNSS, 72-channel receiver, GPS constellation support	■	■	■
	GLONASS/BeiDou/SBAS constellation support (software license)	■****	○	○
	NTP peering		■	■
	IRIG B AM input (IRIG A/B/C37/E AM/DCLS input***)			■
	10 MHz input (1 MHz and 5 MHz input***)			■
	1PPS input (10MPPS input***)			■
Standard network security features	HTTPS/SSL/SSH (with disable function)	SSH	■	■
	SNMP v2/v3 (with disable function)	■	■	■
	IPv4/IPv6/DHCP	■	■	■
	MD5 for NTP		■	■
	Access control lists (one per port)		■	■
	CPU denial of service (DoS) protection through bandwidth limiting		■	■
Security protocol license option	NTP Reflector/Firewall/multi-port with 360,000 NTP requests/second**		○	○
	DoS detection, notification, and protection**		○	○
	RADIUS, TACACS+, LDAP, X.509 certificates		○	○
	NTPv4 Autokey (server and client)		○	○
Interfaces	Four 100/1000BASE-T Ethernet ports		■	■
	Two 10 GbE Ethernet ports		○	○
	One 1000BASE-T PoE port	■		
	Web interface (maximum security cipher suite)		■	■
	Display/Keypad with lockout		■	■
	LEDs: Sync, Network, Alarm		■	■
	RS-232 Console port		■	■
	RS-232 Data/Timing port		■	■
	Alarm relay		■	■
Timing outputs	1PPS output		■	■
	NMEA-0183 output		■	■
	NENA PSAP I/O		■	■
	IRIG B AM/DCLS output (IRIG A/B/C37/E/G/1344/NASA36/2137/XR3 outputs***)			■
	10 MHz output (1 MHz and 5 MHz output***)			■
	Programmable rates output (0.5PPS to 10MPPS, 1PPM)***			○
Miscellaneous	General server status logs (Syslog 1-8 servers)		■	■
	Email alerts		■	■
	Serve NTP in UTC or GPS timescale		■	■
	Alarms, user-configurable	■	■	■
	Customizable login banners		■	■
	Option module slots		0	2
Hardware options	Dual power supplies (AC/AC or DC/DC)		○	○
	OCXO oscillator upgrade		○	○
	Rubidium oscillator upgrade		○	○
	Timing I/O module			○
	Low Phase Noise (standard LPN or Ultra LPN)			○
Software options	Security Protocol license		○	○
	PTP Multi-port/profile grandmaster		○	○
	PTP input		○	○
	GLONASS/BeiDou/SBAS constellation support		○	○
	1PPS time interval measurement			○
	FlexPort™ technology for Timing I/O modules			○

■ Standard feature ○ Optional feature

*Assumes at least one Timing I/O module is installed. See SyncServer Option datasheet for all features and functions of the Timing I/O module and FlexPort license

** NTP Reflector function is included in the Security Protocol license option on S6xx, 1,000 RPS is an option on S80

*** Included in the Timing I/O module FlexPort license option

**** GPS/GLONASS standard, no BeiDou option for S80

SyncServer Model Comparison

SyncServer S600 NTP Network Time Server

Improve security, accuracy, and reliability of time services on the Enterprise IT network with Microsemi's SyncServer S600. This robust time synchronization solution delivers:

- Highly secure NTP solution with Microsemi's security-hardened NTP Reflector technology
- Four GbE LAN ports standard for advanced interoperability and ease-of-use (10 GbE ports optional)
- PTP output with multi-port/profile operations
- High-accuracy NTP hardware time stamping standard
- Easy-to-use modern web interface

S600 Network Time Server



SyncServer S80 Ruggedized/Integrated NTP Server

A fully integrated GPS/GLONASS antenna, receiver, NTP server, and PoE interface that easily integrates into existing PoE infrastructure to immediately be the source of accurate, secure, and reliable time stamps for all network-connected devices.

- Ideal for physical security networks isolated from the Internet that need accurate time stamps
- GbE PoE for easy installation and integration with existing physical security networks
- Environmentally hardened for all weather installations

S80 Network Time Server



SyncServer S650 Time and Frequency Standard

Flexibly deliver "any signal, any connector" time and frequency signals to the mission-critical instrumentation systems with Microsemi's SyncServer S650. Designed for military and aerospace applications, the GPS referenced S650 delivers best-in-class synchronization performance and maximum adaptability. Innovative and highly versatile, this robust time and frequency instrument offers:

- Multi-connector, user-definable output signal configuration, eliminating the need for distribution chassis
- FlexPort™ timing technology for "any signal, any connector" capability
- Low phase noise options for best-in-class LPN performance
- Multiple GbE network ports for easy network configuration and adaptation (10 GbE optional)
- Multiple security-hardened, network-based features for stringent IA requirements

S650 with Timing I/O Modules (Optional Configuration)



Microsemi Corporate Headquarters
 One Enterprise, Aliso Viejo, CA 92656 USA
 Within the USA: +1 (800) 713-4113
 Outside the USA: +1 (949) 380-6100
 Fax: +1 (949) 215-4996
 Email: sales.support@microsemi.com
 www.microsemi.com

©2017 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, California and has approximately 4,800 employees globally. Learn more at www.microsemi.com.

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.